

M613U

ULTRA-HIGH-OUTPUT LED SCOUT LIGHT



1000 LUMENS



1.25 HOURS



213 METERS



DESCRIPTION

The M613U Scout Light generates an impressive 1000 lumens from two 123A batteries. This small, rugged WeaponLight features SureFire's proprietary TIR lens, with a far-reaching, high-intensity beam with ample surround light. The rugged M613U attaches quickly and securely to any MIL-STD-1913 rail via its integral low-profile RM45 mount, which positions the light in the off-set position between the rails of a MIL-STD-1913 (Picatinny) forend, decreasing overall weapon profile and limiting potential snag factor. The light is activated by clicking its pushbutton tailcap switch or, for precision fingertip control without altering your grip on the weapon, by pressing its pressure-activated tape switch (both included). The SR07-D-IT dual remote switch simultaneously controls activation of the M613U and an ATPIAL or DBAL. Constructed of lightweight aerospace aluminum, with a Mil-Spec Hard Anodized finish, and O-ring sealed to keep out the elements, the tough M613U will endure combat-like conditions without any sacrifice in weapon maneuverability.



FEATURES

- Virtually indestructible ultra-high-output LED generates 1000 lumens of blinding light; produces tactical-level light for 1.25 hours on two 123A batteries
- TIR lens shapes versatile beam with enough reach and surround light for medium- to longer-range operations
- Hard Anodized aluminum body, tempered window & O-ring seals make light rugged and durable
- DS-SR07-D-IT waterproof switch assembly includes a system-disable feature, a click-on/off pushbutton switch, and an SR07-D-IT dual remote switch assembly that simultaneously controls activation of the M603V and an ATPIAL or DBAL.
- RM45 mount positions the light in the off-set position between the rails of a MIL-STD-1913 (Picatinny) forend, decreasing overall weapon profile and limiting potential snag factor

PART# / UPC

M613U-BK

084871326995

SPECIFICATIONS

	M613U
COLOR	Black
OUTPUT	1000 lumens
RUNTIME	1.25 hours
PEAK BEAM INTENSITY	11,300 candela
DISTANCE	213 meters
CONSTRUCTION	Aluminum
FINISH	Mil-Spec Hard Anodized
WEIGHT (w/batteries)	7.5 oz. (213 g)
LENGTH	6.2 in (15.75 cm)
BEZEL DIAMETER	1.125 in (2.9 cm)
BATTERIES	Two 123A lithium (incl.)
SWITCHING	Tape switch / click tailcap

All performance claims tested to ANSI/NEMA FL1-2009 Standard.



THE WORLD'S FINEST ILLUMINATION TOOLS, SUPPRESSORS, & TACTICAL PRODUCTS®

18300 Mt. Baldy Circle, Fountain Valley, CA 92708 | 714-545-9444 | Fax: 714-545-9537 | surefire.com

Actual product may vary from photo. Prices and specifications subject to change without notice. | Export of the product(s) shown herein must comply with the appropriate U.S. Government Jurisdiction(s) and Regulation(s).

©2018 SureFire, LLC JUL

FEATURED ACCESSORIES



UE07
7" Momentary-on/off Remote Switch Assembly



UE-SR07
7" Momentary/Constant-on/off Remote Switch Assembly



DS07
7" Momentary-on/off Remote Switch with Constant on/off Tailcap Assembly



DS-SR07
7" Momentary/Constant-on/off Remote Switch with Constant on/off Tailcap Assembly



M75
7" Dual Momentary-on/off Remote Switch for weaponlight + laser device with Constant on/off Tailcap Assembly



M-AD-SF
7" Dual Momentary-on/off Remote Switch for weaponlight + laser device with Constant on/off Tailcap Assembly



123A LITHIUM BATTERIES
Available in 2, 6, 12-packs and bulk options




SF1 SPARE BATTERY CARRIER
Other appropriate models also available

PACKAGING SPECS

BATTERY TYPE	VOLTAGE	CAPACITY	ENERGY	WEIGHT	LITHIUM CONTENT
123A*	3 V	1,550 mAh	4.65 Wh	17 g	0.465 g

*Specifications per battery



TYPE	Box - Kraft Stock
HEIGHT	8 in (20.3 cm)
WIDTH	4.75 in (12.1 cm)
DEPTH	1.75 in (4.4 cm)




SF2R-CB
2 Pack Rechargeable 123A Batteries



SF2R-CHARGEKIT02
Includes: Two Rechargeable 123A Batteries, Battery Charger, AC adapter, 12V DC car plug adapter

BODY SPECS



THE WORLD'S FINEST ILLUMINATION TOOLS, SUPPRESSORS, & TACTICAL PRODUCTS®
18300 Mt. Baldy Circle, Fountain Valley, CA 92708 | 714-545-9444 | Fax: 714-545-9537 | surefire.com

Actual product may vary from photo. Prices and specifications subject to change without notice. | Export of the product(s) shown herein must comply with the appropriate U.S. Government Jurisdiction(s) and Regulation(s).